

Town of Bellingham Fire Department

Fire Prevention Division 508-966-1112



Smoke and Carbon Monoxide Alarm Inspection Checklist *Constructed after February 4, 2011

| Smoke Alarm Requirements: MGL Ch. 148 s. 26E, 26F, 527 CMR 1.00 | | | |
|---|-----|----|--|
| Smoke Alarm Requirements | Yes | No | |
| One Smoke Alarm located inside every bedroom | | | |
| Alarms must be hardwired interconnected with battery backup | | | |
| On every habitable level including basements | | | |
| On ceiling outside each sleeping area | | | |
| On the ceiling at the base of stairs to another occupied level. | | | |
| All Alarms <u>MUST</u> be photoelectric | | | |
| At least one alarm for every 1200 sq. ft. per level | | | |
| Smoke Alarms over 10 years old MUST be replaced | | | |
| Heat Detector in garage | | | |

| Carbon Monoxide Alarm Requirements | Yes | No |
|--|-----|----|
| On every habitable level of the residence including basements | | |
| Within 10' of sleeping area door | | |
| Combination Alarms may be used must have voice notification | | |
| Alarms may be battery, plug in with battery back up hardwired with battery back up | | |
| Follow the manufacturers instruction for placement | | |
| *The usual life span of a Carbon Monoxide Alarm is 5-7 years* | | |
| Is the Address clearly mark with 4" or greater numbers? | | |